

Installation Instructions

Subaru Liberty (2019+) In Dash Mount



Step

Instructions

1

2

Lever and remove lower trim.



Remove 2x screws.



PRODUCT DESIGN SOLUTIONS • EQUIPMENT & BRACKET DESIGN • ELECTRONIC PRODUCT DESIGN • PROTOTYPES • CAD DESIGN & ENGINEERING



3

Remove and unplug A/C vents.



4

Remove 2x screws.





5

Lever and remove A/C unit without unplugging.





6

7

8

Remove 2x screws.



Remove digital display without unplugging.



Place L + R brackets.



PRODUCT DESIGN SOLUTIONS • EQUIPMENT & BRACKET DESIGN • ELECTRONIC PRODUCT DESIGN • PROTOTYPES • CAD DESIGN & ENGINEERING



Replace digital display.



10

9

Replace 4x screws removed in Step 4 and Step 6.



11

Plug in and replace A/C unit, and replace 2x screws removed in Step 2.



PRODUCT DESIGN SOLUTIONS • EQUIPMENT & BRACKET DESIGN • ELECTRONIC PRODUCT DESIGN • PROTOTYPES • CAD DESIGN & ENGINEERING



12

13

Replace plastic trim removed in Step 1.



Plug in and replace A/C vents.





Install front bracket using 4x countersunk screws provided.



If you have any issues or questions, please contact us. Industrial Evolution